

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 2 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

Claims:

No amendments have been made. The following listing of claims is reproduced for the convenience of the Examiner:

Listing of Claims:

1. (original) A nail spacing verification assembly, for use in a nail loading assembly coupled to a nail gun, comprising: a first probe coupled with the nail loading assembly, the first probe for engaging nails in a collated nail strip and determining the spacing of the nails in the collated nail strip; and a second probe coupled with the nail loading assembly and operationally coupled with the first probe, the second probe for engaging with the nails after they have passed the first probe, wherein the second probe in operational concert with the first probe allows the nail to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.
2. (Original) The nail spacing verification assembly of claim 1, wherein the first probe further comprises a first armature coupled with a first axle, wherein the axle enables rotational movement of the first armature and couples the first armature with the nail loading assembly.
3. (Original) The nail spacing verification assembly of claim 1, wherein the second probe further comprises a second armature coupled with a second axle, wherein the axle enables rotational movement of the second armature and couples the second armature with the nail loading assembly.
4. (Original) The nail spacing verification assembly of claim 1, wherein the nail loading assembly is an adjustable angle magazine.
5. (Original) The nail spacing verification assembly of claim 4, wherein the

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 3 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

adjustable angle magazine further comprises a universal adapter assembly.

6. (Original) The nail spacing verification assembly of claim 4, wherein the adjustable angle magazine further comprises a pick-off pivot assembly.
7. (Original) The nail spacing verification assembly of claim 4, wherein the adjustable angle magazine further comprises an articulating pusher assembly.
8. (Original) The nail spacing verification assembly of claim 4, wherein the adjustable angle magazine further comprises a nail shank pawl assembly.
9. (Original) The nail spacing verification assembly of claim 4, wherein the adjustable angle magazine is a top-load magazine or side-load magazine.
10. (Original) The nail spacing verification assembly of claim 1, wherein the nail gun is selected from the group consisting of a spring-loaded nail gun, a pneumatic nail gun, an electro-magnetic nail gun, a combustion nail gun, and a motor driven nail gun.
11. (Original) The nail spacing verification assembly of claim 1, wherein the nail gun further comprises a clutch assembly.
12. (Original) A nail spacing verification assembly, for use in a nail loading assembly coupled to a nail gun, comprising:
a first spring loaded probe coupled with the nail loading assembly, the first spring loaded probe for engaging nails in a collated nail strip and determining the spacing of the nails in the collated nail strip; and
a second probe coupled with the nail loading assembly and operationally coupled with the first spring loaded probe, the second probe for engaging with the nails after they have passed the first spring loaded probe,

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 4 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

wherein the second probe in operational concert with the first spring loaded probe allows the nails to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.

13. (Original) The nail spacing verification assembly of claim 12, wherein the first probe further comprises a first sleeve coupled with a first axle, the first sleeve is further coupled with a spring assembly which couples with a first armature, wherein the axle enables rotational movement of the first sleeve and first armature and couples the first sleeve with the nail loading assembly.
14. (Original) The nail spacing verification assembly of claim 12, wherein the second probe further comprises a second armature coupled with a second axle, wherein the axle enables rotational movement of the second armature and couples the second armature with the nail loading assembly.
15. (Original) The nail spacing verification assembly of claim 12, wherein the nail loading assembly is an adjustable angle magazine.
16. (Original) The nail spacing verification assembly of claim 15, wherein the adjustable angle magazine further comprises a universal adapter assembly.
17. (Original) The nail spacing verification assembly of claim 15, wherein the adjustable angle magazine further comprises a pick-off pivot assembly.
18. (Original) The nail spacing verification assembly of claim 15, wherein the adjustable angle magazine further comprises an articulating pusher assembly.
19. (Original) The nail spacing verification assembly of claim 15, wherein the adjustable angle magazine further comprises a nail shank pawl assembly.

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 5 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

20. (Original) The nail spacing verification assembly of claim 15, wherein the adjustable angle magazine is a top-load magazine or side-load magazine.
21. (Original) The nail spacing verification assembly of claim 12, wherein the nail gun is selected from the group consisting of a spring-loaded nail gun, a pneumatic nail gun, an electro-magnetic nail gun, a combustion nail gun, and a motor driven nail gun.
22. (Original) The nail spacing verification assembly of claim 12, wherein the nail gun further comprises a clutch assembly.
23. (Original) An adjustable angle magazine for use with a nail gun, comprising:
a housing including a first end and a second end, the housing for storing and providing nails in a collated nail strip to a nail driving assembly of the nail gun;
an adjustment assembly disposed proximal to the second end of the housing, the adjustment assembly for affixing the position of the housing relative to the nail gun;
a universal adapter assembly coupled with the first end of the housing, the universal adapter assembly for pivotally coupling with the nail driving assembly; and
a nail spacing verification assembly disposed upon the housing, the nail spacing verification assembly for engaging the nails in the housing,
wherein the nail spacing verification assembly allows the nails to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.
24. (Original) The adjustable angle magazine of claim 23, wherein the nail spacing verification assembly is a first nail spacing verification assembly comprising:
a first probe coupled with the housing, the first probe for engaging nails in a collated nail strip and determining the spacing of the nails in the collated nail strip; and
a second probe coupled with the housing and operationally coupled with the first probe, the second probe for engaging with the nails after they have passed the first probe,

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 6 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

wherein the second probe in operational concert with the first probe allows the nail to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.

25. (Original) The adjustable angle magazine of claim 23, wherein the nail spacing verification assembly is a second nail spacing verification assembly comprising:
a first spring loaded probe coupled with the housing, the first spring loaded probe for engaging nails in a collated nail strip and determining the spacing of the nails in the collated nail strip; and

a second probe coupled with the housing and operationally coupled with the first spring loaded probe, the second probe for engaging with the nails after they have passed the first spring loaded probe,

wherein the second probe in operational concert with the first spring loaded probe allows the nails to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.

26. (Original) The adjustable angle magazine of claim 23, further comprising an articulating pusher assembly.

27. (Original) The adjustable angle magazine of claim 23, further comprising a nail shank pawl assembly.

28. (Original) The adjustable angle magazine of claim 23, wherein the adjustable angle magazine is a top-load magazine or side-load magazine.

29. (Original) The adjustable angle magazine of claim 23, wherein the nail gun is selected from the group consisting of a spring-loaded nail gun, a pneumatic nail gun, an electro-magnetic nail gun, a combustion nail gun, and a motor driven nail gun.

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 7 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

30. (Original) The adjustable angle magazine of claim 23, wherein the nail gun is selected from the group consisting of a spring-loaded nail gun, a pneumatic nail gun, an electro-magnetic nail gun, a combustion nail gun, and a motor driven nail gun.
31. (Original) The adjustable angle magazine of claim 23, wherein the nail gun further comprises a clutch assembly.
32. (Original) An adjustable angle nail gun, comprising:
a handle including a first end and a second end, the second end coupled with a fastening assembly;
a nail driving assembly coupled with the first end of the handle, the nail driving assembly including a driver blade, the nail driving assembly for driving nails in a collated nail strip;
an adjustable angle nose casting assembly coupled with the nail driving assembly, the adjustable angle nose casting assembly for receiving the nail and enabling the operational engagement of the driver blade with the nail;
an adjustable angle magazine including a first end coupled with a universal adapter assembly for pivotally coupling with the adjustable angle nose casting assembly and an adjustment assembly disposed proximal to a second end of the adjustable angle magazine, the adjustment assembly for coupling with the fastening assembly, the adjustable angle magazine for storing and providing the nails to the adjustable angle nose casting assembly,
a nail spacing verification assembly disposed upon the housing, the nail spacing verification assembly for engaging the nails in the housing,
wherein the nail spacing verification assembly allows the nails to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 8 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

33. (original) The adjustable angle nail gun of claim 32, wherein the nail spacing verification assembly is a second nail spacing verification assembly comprising:

a first probe coupled with the adjustable angle magazine, the first probe for engaging nails in a collated nail strip and determining the spacing of the nails in the collated nail strip; and

a second probe coupled with the adjustable angle magazine and operationally coupled with the first spring loaded probe, the second probe for engaging with the nails after they have passed the first probe,

wherein the second probe in operational concert with the first probe allows the nails to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.

34. (original) The adjustable angle nail gun of claim 32, wherein the nail spacing verification assembly is a second nail spacing verification assembly comprising:

a first spring loaded probe coupled with the adjustable angle magazine, the first spring loaded probe for engaging nails in a collated nail strip and determining the spacing of the nails in the collated nail strip; and

a second probe coupled with the adjustable angle magazine and operationally coupled with the first spring loaded probe, the second probe for engaging with the nails after they have passed the first spring loaded probe,

wherein the second probe in operational concert with the first spring loaded probe allows the nails to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.

35. (original) The adjustable angle nail gun of claim 32, wherein the adjustable angle magazine further comprises a pick-off pivot assembly.

36. (original) The adjustable angle nail gun of claim 32, wherein the adjustable angle magazine further comprises an articulating pusher assembly.

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 9 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

37. (original) The adjustable angle nail gun of claim 32, wherein the adjustable angle magazine further comprises a nail shank pawl assembly.
38. (original) The adjustable angle nail gun of claim 32, wherein the adjustable angle magazine is a top-load magazine or side-load magazine.
39. (original) The adjustable angle nail gun of claim 32, wherein the adjustable angle nail gun is selected from the group consisting of a spring-loaded nail gun, a pneumatic nail gun, an electro-magnetic nail gun, a combustion nail gun, and a motor driven nail gun.
40. (original) The adjustable angle nail gun of claim 32, wherein the adjustable angle nail gun further comprises a clutch assembly.
41. (Original) A nail spacing verification assembly for use with a nail loading assembly of a nail gun, comprising:
means for determining the spacing between nails of a collated nail strip in the nail loading assembly and allowing the nails to advance when the spacing of the nails in the collated nail strip is determined to be correct for use by the nail gun.
42. (Original) The nail spacing verification assembly of claim 41, wherein the means for determining spacing and allowing advancement is a nail spacing verification assembly disposed upon the nail loading assembly.
43. (Original) The nail spacing verification assembly of claim 41, wherein the nail loading assembly is an adjustable angle magazine.
44. (Original) The nail spacing verification assembly of claim 43, wherein the adjustable angle magazine further comprises a universal adapter assembly.

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 10 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

45. (Original) The nail spacing verification assembly of claim 43, wherein the adjustable angle magazine further comprises a pick-off pivot assembly.
46. (Original) The nail spacing verification assembly of claim 43, wherein the adjustable angle magazine further comprises an articulating pusher assembly.
47. (Original) The nail spacing verification assembly of claim 43, wherein the adjustable angle magazine further comprises a nail shank pawl assembly.
48. (Original) The nail spacing verification assembly of claim 43, wherein the adjustable angle magazine is a top-load magazine or side-load magazine.
49. (Original) The nail spacing verification assembly of claim 41, wherein the nail gun is selected from the group consisting of a spring-loaded nail gun, a pneumatic nail gun, an electro-magnetic nail gun, a combustion nail gun, and a motor driven nail gun.
50. (Original) The nail spacing verification assembly of claim 41, wherein the nail gun further comprises a clutch assembly.
- 51-56. (cancelled).
57. (previously presented) A spacing verifier for use in a fastening power tool, the spacing verifier comprising:
- a first member coupled to the fastening power tool, the first member configured to determine spacing between at least two fasteners in a strip; and
 - a second member coupled to the fastening power tool, the second member operationally coupled to the first member for engaging one fastener of the at least two fasteners after the one fastener has passed the first member,

Applicant : John W. Schnell
Serial No. : 10/665,094
Filed : September 17, 2003
Page : 11 of 14

Attorney Docket No. JK01463E
Art Unit: 3726
Examiner: Hong, John C.

wherein the second member is configured to prevent advancement of the one fastener when the spacing between the at least two fasteners is determined to be less than a predetermined value.

58. (previously presented) The spacing verifier of claim 57 wherein the first member comprises a probe.

59. (previously presented) The spacing verifier of claim 58 wherein the probe comprises an armature coupled to an axle of the fastening power tool.

60. (previously presented) The spacing verifier of claim 59 wherein the probe comprises a spring-biased member coupled to the armature.

61. (previously presented) The spacing verifier of claim 57 wherein the second member comprises a probe.

62. (previously presented) The spacing verifier of claim 61 wherein the probe comprises an armature coupled to an axle of the fastening power tool.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.